

TSR BALE

SIR 10 Premium TSR

Premium Indonesian TSR with dirt at or below 0.10%, ash at or below 0.75%, Mooney ML 61 plus or minus 5.

SIR 10

Tire



- Lower dirt and ash than SIR 20 for premium tread lines
- 35 kg shrink-wrapped bales, same handling as SIR 20
- Mooney ML (1+4) at 100 °C: 61 plus or minus 5
- Graded to SNI 1903 SIR 10 tables with per-lot COA

SPECIFICATIONS

Dirt content	≤ 0.10% (w/w)	Mooney viscosity	ML (1+4) 100 °C: 61 ± 5
Ash content	≤ 0.75% (w/w)	Minimum order	19.6 MT (1 × 20 ft FCL, 560 bales)
Volatile matter	≤ 0.80% (w/w)	Packaging	35 kg bales, shrink-wrapped pallet (1,260 kg N.W. per unit)
Nitrogen	≤ 0.60% (w/w)	Lead time	2–3 weeks FOB Jakarta / Belawan
Plasticity retention index (PRI)	≥ 50		

EXPORT DETAILS

HS CODE	INCOTERMS	CERTIFICATIONS				
4001.22	FOB · CIF · CFR	SNI 1903	ISO 9001	ISO 14001	ISO 45001	Halal (BPJPH)

PRODUCT OVERVIEW

SIR 10 is the premium Indonesian TSR grade for tire tread and thin-gauge compounds that need lower dirt and ash than SIR 20. PRI is at or above 50 and Mooney ML (1+4) at 100 °C is centred at 61. Same 35 kg bale format and 19.6 MT container MOQ as SIR 20.

Values are typical specifications for the current production period and are confirmed lot by lot on the sales contract. Laboratory records travel with every shipment.

PT FoodHub Collective Indonesia

Jl. Tb Simatupang Kav. 1, Pasar Minggu
Jakarta Selatan 12560, Indonesia

sales@indonesia-rubber.com

+62 896 7558 3987
indonesia-rubber.com



Scan for the full
product page