

TSR BALE

SIR 20 TSR Tire Grade

Workhorse Indonesian TSR bale with dirt at or below 0.16%, PRI at or above 50, Mooney ML 65 plus or minus 5.

SIR 20

Tire



- SNI 1903 tire-grade TSR with PRI at or above 50
- 19.6 MT FCL, 560 bales of 35 kg on export pallets
- Dirt, ash, Mooney, and PRI confirmed per lot before stuffing
- FOB Jakarta or Belawan with full export documentation

SPECIFICATIONS

Dirt content	≤ 0.16% (w/w)	Mooney viscosity	ML (1+4) 100 °C: 65 ± 5
Ash content	≤ 1.00% (w/w)	Minimum order	19.6 MT (1 × 20 ft FCL, 560 bales)
Volatile matter	≤ 0.80% (w/w)	Packaging	35 kg bales, shrink-wrapped pallet (1,260 kg N.W. per unit)
Nitrogen	≤ 0.60% (w/w)	Lead time	2–3 weeks FOB Jakarta / Belawan
Plasticity retention index (PRI)	≥ 50		

EXPORT DETAILS

HS CODE	INCOTERMS	CERTIFICATIONS			
4001.22	FOB · CIF · CFR	SNI 1903	ISO 9001	ISO 14001	ISO 45001
					Halal (BPJPH)

PRODUCT OVERVIEW

SIR 20 is the standard Indonesian tire-grade TSR for passenger and light-truck compounds. Bales are graded to SNI 1903 with dirt content at or below 0.16%, ash at or below 1.00%, and Mooney viscosity ML (1+4) at 100 °C centred at 65. Shrink-wrapped 35 kg bales load 19.6 MT per 20 ft container from Jakarta or Belawan.

Values are typical specifications for the current production period and are confirmed lot by lot on the sales contract. Laboratory records travel with every shipment.

PT FoodHub Collective Indonesia

Jl. Tb Simatupang Kav. 1, Pasar Minggu
Jakarta Selatan 12560, Indonesia

sales@indonesia-rubber.com

+62 896 7558 3987
indonesia-rubber.com



Scan for the full
product page