

TSR BALE

SIR 5 Premium Light TSR

Ultra-clean coagulum TSR with dirt at or below 0.05%, PRI at or above 60, Lovibond colour index at or below 6.

SIR 5

Tire



- Dirt at or below 0.05%, PRI at or above 60
- Lovibond colour index at or below 6 for light-color tread
- Premium light coagulum grade between SIR 3L and SIR 10
- 35 kg shrink-wrapped bales, 19.6 MT FCL

SPECIFICATIONS

Dirt content	≤ 0.05% (w/w)	Lovibond colour index	Lovibond ≤ 6 (individual)
Ash content	≤ 0.60% (w/w)	Minimum order	19.6 MT (1 × 20 ft FCL, 560 bales)
Volatile matter	≤ 0.80% (w/w)	Packaging	35 kg bales, shrink-wrapped pallet (1,260 kg N.W. per unit)
Nitrogen	≤ 0.60% (w/w)	Lead time	3–4 weeks FOB Jakarta / Belawan
Plasticity retention index (PRI)	≥ 60		

EXPORT DETAILS

HS CODE	INCOTERMS	CERTIFICATIONS				
4001.22	FOB · CIF · CFR	SNI 1903	ISO 9001	ISO 14001	ISO 45001	Halal (BPJPH)

PRODUCT OVERVIEW

SIR 5 is a premium light coagulum TSR grade between SIR 3L field-latex lots and SIR 10 volume premium tread. Dirt content is at or below 0.05%, ash at or below 0.60%, PRI at or above 60, and Lovibond colour is held at or below 6 per SNI 1903. Same 35 kg bale format and 19.6 MT container MOQ as other Indonesian TSR exports.

Values are typical specifications for the current production period and are confirmed lot by lot on the sales contract. Laboratory records travel with every shipment.

PT FoodHub Collective Indonesia

Jl. Tb Simatupang Kav. 1, Pasar Minggu
Jakarta Selatan 12560, Indonesia

sales@indonesia-rubber.com

+62 896 7558 3987
indonesia-rubber.com



Scan for the full
product page